



ISO CERT NO. 160067



ISO CERT NO. 190018

# FALCHEM D-LUBE

AEROSOL DRY FILM LUBRICANT

**D - LUBE is a tough dry moly sulfide lubricant specially formulated for use in all applications where a high pressure, high temperature, DRY lubricant is desired.**

**NO DRIPPING OR SLINGING-** D-LUBE forms a tough dry coating that adheres to metal surfaces and will not dip or sling off even subjected to centrifugal forces.

**LUBRICATES AND PROTECTS** – Excellent for use as a lubricant where conventional oils and greases are not suitable. Moly contents plate out filling asperities normally present even on highly polished surfaces. This prevents abrasion from metal-to-metal contact.

**RESISTS DUST AND ABRASIVE PARTICLES** – D-LUBE offers outstanding dry coating protection even under great pressures. It does not attract abrasive particles which cause dangerous friction, wear and damages.

**EXCELLENT ANTI-RUST PROPERTIES** – Helps protect metal surfaces against moisture which causes rust and corrosion and other industrial contaminants.

**SAFE TO USE** – D-LUBE is non-flammable, non conductive and will not harm metals, most plastics, leather, rubber and other elastomers.

**RESIST HIGH TEMPERATURE AND PRESSURES** – D-LUBE remains stable within temperatures from – 180°C to 410°C and cannot be squeezed out even up to 6,500 atm (100,000 psi).

## WHERE USED

In all areas where friction presents a problem, i.e., hinges, pins, thread parts, pistons, cylinders, valves, gears, cams, latches, actuators, printing machinery, playground equipment.

**D-LUBE** is ideal for use to replace graphite in many situations i.e., on hinges or areas in heating operations, or metal slides and rollers in kilns and ovens.

**D-LUBE** is also widely used in the mining, aerospace, textile, marine, transportation, metal working, construction, and petroleum and cold storage industries.

Commercial complexes, schools, hotels, military camp, power stations, industrial plants and apartment complexes use D-LUBE for locks, doors, hinges sliding devices, fences and hard to reach surfaces.

## INSTRUCTIONS

Shake can vigorously. Spray from a distance in a sweeping manner on dry and clean surfaces where treatment is desired. Before storing after each use, inverts can and spray a short jet to clear nozzle.

Note: **Two thin coats are more effective than one thick coat.**

## TECHNICAL DATA

**Description:** Molybdenum disulphide, inhibitor, Resin binder, PTFE and propellant.

**Flammability:** Non-flammable.

**Appearance:** Dry Film lubricant.



ISO CERT NO. 160067



ISO CERT NO. 190018

**SAFETY AND HANDLING**

<b>HANDLING</b>	Handle with care. Store in dry, cool and well ventilated environment.
<b>SAFETY</b>	<b>IMMEDIATE ACTIONS</b>
<b>Eye Contact</b>	Avoid Eye Contact. Otherwise, flush with plenty of water for a few minutes. Seek medical attention.
<b>Skin Contact</b>	Avoid Skin contact. Otherwise, wash contaminated area thoroughly with water. Seek medical attention.
<b>Inhalation</b>	Do not breathe gas/vapors. Otherwise, seek fresh air source at once. Seek medical attention. In case of insufficient ventilation, wear suitable respiratory equipment..
<b>If Swallowed</b>	Avoid ingestion. Otherwise, consume considerable quantity of water. Do not induce vomiting. Seek medical attention.
<b>General instructions</b>	Avoid spillage, splashing and mishandling. Precautionary measures for body protection are strongly recommended before use.

**PACKING SIZE: 25 LITER, 200 LITERS PAIL/DRUM**

**Read the Material Safety Data Sheet before using this product**

For detailed information on safety and health, please refer to Material Safety Data Sheet and/or product label.

**ENERCHEM (S) PTE LTD (Manufacturer of trademark FALCHEM®)** of or any subsidiaries or associated companies warranties of merchantability and competence, if any, along with any expressed warranties concerning this merchandise, shall not be actionable or pertinent or effective if goods is used contrarily or differently to the directions herein and in no other way may due to impending hazards from inappropriate use of the good explained herein. Merchants might vary insubstantially depending on country of origin. The information provided concerning merchandise is exclusively presented to the customer.