



ISO CERT NO. 160067



ISO CERT NO. 190018

KOOL - TAP

HIGH PERFORMANCE CUTTING, TAPPING COMPOUND

- **OUTSTANDING STRAYING PROPERTY** - Specially blended chlorinated paraffin and sulfurized oil stays well without sling off, ensures high efficiency with soft metals like brass or with the difficult stainless steels. Superior lubrication results in faster cutting rate.
- **DEEP PENETRATION** – Allows complete lubrication on hard to reach areas such as the inner threading of pipes.
- **LUBRICATES & COOLS** – Special propellant evaporates to allow good cooling while resulting in faster, timesaving operations.
- **VERSATILE** – Packed ideally for manual or site work where built-in tool lubrication is not available.
- **EXTEND TOOL LIFE** – Heat is reduced at source, thus prevents tool breakage. Inhibited formula prevents flash rusting of tools at work.

WHERE USED

Ideal for any metal cutting operation; pipe threading, drill press, saw, tapping, milling machine operation, precision tooling, reaming and other operations for which the application of bulk fluid is not convenient of suitable.

INSTRUCTIONS

Shake can well before use. Spray directly at parts to be lubricated. Handy pin-point extension nozzle allows accurate and non waste application.

BENEFITS:

Double tool life, Double die life, Results in better finishers, Results in closer tolerances, Increases cutter life, Increases number of job done per tool grind, Increases number of holes with each tapping job, Less broaching time, Less breakage time, Less tool wear, Less down-time & Faster job done.



ISO CERT NO. 160067



ISO CERT NO. 190018

SAFETY AND HANDLING

HANDLING	Handle with care. Store in dry, cool and well ventilated environment.
SAFETY	IMMEDIATE ACTIONS
Eye Contact	Avoid Eye Contact. Otherwise, flush with plenty of water for a few minutes. Seek medical attention.
Skin Contact	Avoid Skin contact. Otherwise, wash contaminated area thoroughly with water. Seek medical attention.
Inhalation	Do not breathe gas/vapors. Otherwise, seek fresh air source at once. Seek medical attention. In case of insufficient ventilation, wear suitable respiratory equipment..
If Swallowed	Avoid ingestion. Otherwise, consume considerable quantity of water. Do not induce vomiting. Seek medical attention.
General instructions	Avoid spillage, splashing and mishandling. Precautionary measures for body protection are strongly recommended before use.

PACKING SIZE: 25 LITER, 200 LITERS PAIL/DRUM

Read the Material Safety Data Sheet before using this product

For detailed information on safety and health, please refer to Material Safety Data Sheet and/or product label.

ENERCHEM (S) PTE LTD (Manufacturer of trademark FALCHEM®) of or any subsidiaries or associated companies warranties of merchantability and competence, if any, along with any expressed warranties concerning this merchandise, shall not be actionable or pertinent or effective if goods is used contrarily or differently to the directions herein and in no other way may due to impending hazards from inappropriate use of the good explained herein. Merchants might vary insubstantially depending on country of origin. The information provided concerning merchandise is exclusively presented to the customer.