



ISO CERT NO. 160067



ISO CERT NO. 190018

FALCHEM MUD & SILT DISPERSANT

DESCRIPTION:

MUD & SILT DISPERSANT is a concentrated liquid solution formulated with a high molecular weight polymer component, special surfactants and a corrosion inhibitor in order to fight formations and disperse accumulations of mud and silt in ballast water tanks. Actually, **MUD & SILT DISPERSANT** reacts with mud and silt to form large non-adhering particles, which are dissolved in the tank and then discharged with the ballast water during de-ballasting.

CHARACTERISTICS, ADVANTAGES & APPLICATIONS:

- Ideal for the removal, dispersion and prevention of heavy mud, loose scale, rust deposits, silt accumulates and other sediments in ballast water tanks.
- Reacts with mud and silt molecules to form non-adhering particles, which are easily discharged during de-ballasting.
- Terminates microorganisms harvested in the mud and silt sludge.
- Effectively cleans the ballast water tank lines and pumping equipment.
- Prevents extensive erosion from the ballast tank surfaces and cavities.
- Acts quickly and efficiently and is water-soluble
- Non-flammable and non-toxic.
- Can safely be applied to all metals except those galvanized and those made of tin, zinc and aluminum.
- Cost effective, easy to apply and use.
- The product is non-toxic and evaluation of LC 50* value meets the IMO regulations.

TYPICAL PHYSICAL PROPERTIES

Color	: Colorless
Specific gravity (25°C)	: 1.01
Flash Point	: Not applicable

APPLICATION

A. Dosing Procedure

Commonly, a quantity of 25-50 liters of **MUD & SILT DISPERSANT** per 1000 tons of ballast water content is used every time the tanks are ballasted. However, when we deal with heavy mud and silt accumulations, 150-250 liters per 1000 tons of ballast water is recommended for fast and complete cleaning.

B. Cleaning Procedure

In the case where regular treatment is desired, the prescribed quantity of **MUD & SILT DISPERSANT** is added to ballast water, while ballasting, in order to make sure of the homogeneity of the formed mixture. Here, the treatment must be repeated every time the tanks are ballasted. In the case of heavy mud and silt accumulation, the quantity of **MUD & SILT DISPERSANT** prescribed is poured in the de-ballasted tanks, which now are filled only with 20-30 cm of their height capacity with water, being enough to ensure mud and silt removal by rapid agitation. Then, the mixture must be left to act for a period of 3-5 hours followed by complete removal. Note that a high-pressure water supply may be used to assist removal and further penetration into the mud and silt deposits. Also, the treatment may have to be repeated depending on the degree of contamination and accumulation we are dealing with.



ISO CERT NO. 160067



ISO CERT NO. 190018

SAFETY AND HANDLING

HANDLING	Handle with care. Store in dry, cool and well ventilated environment.
SAFETY	IMMEDIATE ACTIONS
Eye Contact	Avoid Eye Contact. Otherwise, flush with plenty of water for a few minutes. Seek medical attention.
Skin Contact	Avoid Skin contact. Otherwise, wash contaminated area thoroughly with water. Seek medical attention.
Inhalation	Do not breathe gas/vapors. Otherwise, seek fresh air source at once. Seek medical attention. In case of insufficient ventilation, wear suitable respiratory equipment..
If Swallowed	Avoid ingestion. Otherwise, consume considerable quantity of water. Do not induce vomiting. Seek medical attention.
General instructions	Avoid spillage, splashing and mishandling. Precautionary measures for body protection are strongly recommended before use.

PACKING SIZE: 25 LITER, 200 LITERS PAIL/DRUM

Read the Material Safety Data Sheet before using this product

For detailed information on safety and health, please refer to Material Safety Data Sheet and/or product label.

ENERCHEM (S) PTE LTD (Manufacturer of trademark FALCHEM®) of or any subsidiaries or associated companies warranties of merchantability and competence, if any, along with any expressed warranties concerning this merchandise, shall not be actionable or pertinent or effective if goods is used contrarily or differently to the directions herein and in no other way may due to impending hazards from inappropriate use of the good explained herein. Merchants might vary insubstantially depending on country of origin. The information provided concerning merchandise is exclusively presented to the customer.